## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

2

3

4

5

6

7

8

9

10

11

12

2

3

Claim 1 (currently amended): An information processing terminal which is connected onto a network to which a plurality of <u>additional</u> information processing terminals are connected, and transmits a signal when it acquires a transmission privilege on the network, comprising:

a bus status detecting means for detecting whether said network is busy or idle;

a counting means for repeating count-up to reach a idle time unit if the network is idle as a

detected result of said bus status detecting means, wherein a node ID of said information processing terminal is set to be equal to a default node ID0;

a control means for managing a parameter incremented whenever the idle time unit is

a control means for managing a parameter incremented whenever the idle time unit is detected as a result of count-up by said counting means and creating a transmission frame when said parameter is equal to said node ID of said information processing terminal agrees with its own node ID having a default node ID0 allotted to each node as an initial value; and

a transmitting means for transmitting the transmission frame created by said control means.

Claim 2 (currently amended): An information processing terminal according to claim 1, further comprising a receiving means for receiving the transmission frame,

wherein said transmission frame transmitted from one of said additional the other information

4 processing terminal terminals connected to said network includes the default node ID0, and

said control means extracts the default node ID0 included in the transmission frame received by said receiving means and updates said parameter to said default node ID0.

Claim 3 (currently amended): An information processing terminal according to claim 2, further comprising a synchronizing error detecting means for detecting within its own terminal an error which affects the synchronization with <u>said one of said additional</u> the other information processing terminal terminals on said network and relates to counting of said parameter,

wherein when the error is detected by said synchronizing error detecting means, said control means sets said node ID of said information processing terminal to be equal to a sum of said default node ID0 and a maximum node number n its new own node ID at the sum of a prescribed value enough to continue the period dedicated to reception for a prescribed time and said default node ID0, and thereafter when said transmission frame is normally received by said receiving means, said control means updates said parameter to said default node ID0 included in said transmission frame.

Claim 4 (currently amended): An information processing terminal according to one of claims 1 to 3, having a transmission privilege providing system wherein a A transmission privilege rounding system wherein a plurality of information processing terminals one of which is defined by one of claims 1 to 3 are connected to the same network, and said transmission privilege is provided to each of rounded among said information processing terminal and said plurality of

6

additional information processing terminals one at a time.

1	Claim 5 (currently amended): A method for providing rounding a transmission
2	privilege to each of a plurality of nodes one at a time, said plurality of nodes being connected on a
3	network to which a plurality of nodes are connected, comprising the steps to be carried out by each
4	of said nodes of:
5	detecting whether said network is busy or idle, repeating count-up to reach an idle time unit
6	if said network is idle, and
7	incrementing a parameter whenever said idle time is detected;
8	transmitting the transmission frame inclusive of the node ID if said parameter agree with the
9	node ID;
10	extracting said node ID included in said transmission frame when said transmission frame
11	is received from the network and updating said parameter to said node ID.
1	Claim 6 (original): A computer-readable transmission privilege acquisition program
2	loaded in a node which can transmit a signal onto a network to which a plurality of nodes are
3	connected when each node acquires a transmission privilege, said program causing a computer to
4	execute:
5	processing of detecting whether said network is busy or idle;
6	processing of repeatedly counting to reach a idle time unit if said network is idle;

processing of incrementing a parameter whenever said idle time is detected, thereby creating

- a transmission frame inclusive of the node ID if said parameter agree with the node ID; and
- processing of transmitting the transmission frame thus created.

\* \* \* \*